

Dephasing and thermal smearing in an electromechanical which-path device

A. D. Armour,^{a,*} M. P. Blencowe^b

^a*Blackett Laboratory, Imperial College, London SW7 2BW, U.K.*

^b*Department of Physics and Astronomy, Dartmouth College, Hanover, New Hampshire 03755*

Abstract

In an electromechanical which-path device electrons travelling through an Aharonov–Bohm ring with a quantum dot in one of the arms are dephased by an interaction with the fundamental flexural mode of a radio-frequency cantilever, leading to a reduction in the visibility of interference fringes. However, at finite temperatures time-averaged measurement of the current leads to a fringe visibility which is reduced partly by dephasing of the electrons and partly by a thermal smearing effect. The balance between the thermal smearing and dephasing predicted by a calculation depends very strongly on the choice of cantilever basis states used. The interaction between the cantilever and its environment is expected to select the coherent state basis for the cantilever and hence lead to a dephasing rate which is substantially lower than that which would arise if instead the Fock states were selected.

Key words: Which-path device, Decoherence, Micromechanical systems

PACS: 85.35.Ds, 73.63.Kv, 73.23.Hk

* Corresponding author: Fax: +44-(0)-20-7594-7604, email: a.armour@ic.ac.uk

In a which-path experiment an external measuring device is used to probe for the presence of a particle in one of two interfering paths which the particle can take. Complementarity requires that any knowledge gained about the path taken by a particle must be accompanied by a loss of interference fringe visibility, thus which-path systems provide an ideal testing ground for theoretical ideas about dephasing. In the solid-state an Aharonov-Bohm (AB) ring may be used to produce interfering paths for electrons; which-path measurements can then be performed by incorporating a quantum dot on one arm of the ring and introducing an external device which couples to the occupancy of the dot (i.e. by an electrostatic interaction). Buks *et al.*[1] demonstrated a solid-state which-path device by using the current through a quantum point contact adjacent to the dot to probe the dot's occupancy.

Recently, we developed a theoretical model to describe an electromechanical version of the which-path experiment[2]. We considered a system consisting of an AB ring with a quantum dot on one arm, similar to that used by Buks *et al.*, but with a cantilever positioned so that its tip lies just above the dot as opposed to a quantum point contact. If the cantilever is at a high enough voltage with respect to the dot then it can act as a which-path detector: the presence (and absence) of the additional electron on the dot in the Coulomb blockade regime couples to the flexural modes of the cantilever. It turns out that at sufficiently low temperatures only the lowest flexural mode of the cantilever is relevant and so it can be treated as a single-mode quantum oscillator.

In the theory, we assumed that the cantilever was initially in a thermal mixture of states so that the overall fringe visibility is obtained by summing over the elastic transmission for a complete set of cantilever states[2]. The reduction in fringe visibility which we obtain from the thermally weighted average

is composed of two parts: the magnitudes of the elastic transmission for each cantilever state are reduced by the dephasing caused by the cantilever and the phase of the transmission differs for each cantilever state. When the average is taken the phase differences cause a further reduction in magnitude (an effect which we term thermal smearing). Thus in calculating the thermally averaged transmission, we can predict the time-independent fringe visibility, but we are not able to predict how much dephasing the cantilever causes. Here we investigate the distinction between contributions to the reduction in interference fringe visibility from the cantilever-induced dephasing of the electron and thermal smearing. We calculate the elastic transmission for the cantilever initially in a pure Fock state, as well as the case where the cantilever is in a pure coherent state which we considered before. The dephasing induced by the cantilever is strongly dependent on the state it is in, but a thermal average leads to a unique result and so does not of itself give complete information about the dephasing induced by the cantilever.

The key quantity in the theory is the elastic transmission amplitude of the arm containing the dot, $\langle t_{QD}(\epsilon) \rangle$, for a given electron energy in the leads, ϵ , since it determines the visibility of the interference fringes. For a cantilever in the pure state $|a\rangle$, the elastic transmission takes the form

$$\langle a|t_{QD}(\epsilon)|a\rangle = -\Gamma \int_0^\infty \frac{d\tau}{\hbar} e^{[i(\epsilon-\epsilon_0)-\Gamma/2]\tau/\hbar} \langle \Phi(\tau) \rangle,$$

where $\hbar/\Gamma$ is the characteristic dwell time of the electron on the dot, ϵ and ϵ_0 are the energies of the electrons incident on the dot and the relevant energy level in the dot respectively, and the cantilever dependent term is

$$\langle \Phi(t) \rangle = \langle a|e^{i\omega c^\dagger ct} e^{-i\omega c^\dagger ct + i\lambda(c^\dagger + c)t/\hbar}|a\rangle$$

where c operates on the fundamental flexural mode of the cantilever with frequency ω and λ is the strength of the (linear) coupling between the cantilever and the electron on the dot.

The value of the elastic transmission is strongly dependent on the state of the cantilever. For a pure coherent state, $|\nu\rangle$, the cantilever dependent part of the transmission, $\langle\Phi(t)\rangle$, takes the form[2],

$$\langle\nu|\Phi(t)|\nu\rangle = e^{i(\lambda/\hbar\omega_0)^2[\omega_0\tau - \sin(\omega_0\tau)]} e^{-(\lambda/\hbar\omega_0)^2[1 - \cos(\omega_0\tau)]} e^{(\lambda/\hbar\omega_0)(\nu^*\mu - \nu\mu^*)},$$

where $\mu = e^{i\omega_0 t} - 1$. In contrast, if the cantilever is in a Fock state $|n\rangle$ then $\langle\Phi(t)\rangle$ is given by[3]

$$\begin{aligned} \langle n|\Phi(t)|n\rangle &= e^{i(\lambda/\hbar\omega_0)^2[\omega_0\tau - \sin(\omega_0\tau)]} e^{-(\lambda/\hbar\omega_0)^2[1 - \cos(\omega_0\tau)]} \\ &\times L_n(2(\lambda/\hbar\omega_0)^2[1 - \cos(\omega_0\tau)]), \end{aligned}$$

where $L_n(x)$ is a Laguerre polynomial of order n .

For given values of the electron energies and lifetimes on the dot, the elastic transmission is a function of the cantilever's state and the strength of the cantilever-dot coupling, λ . When there is a finite coupling between the cantilever and the dot, the transmission amplitude is reduced in magnitude and receives a phase shift (i.e. a finite argument). The reduction in magnitude is readily interpreted as dephasing of the electron, but it can also be associated with the detection by the cantilever of the path taken by the electron.

The thermally averaged elastic transmission is independent of the basis in which the average is performed, but when we examine the terms that contribute to the average, the balance between dephasing and thermal smearing varies considerably. In the Fock basis, the phase shift induced by the cantilever

does not vary significantly with either the particular state, $|n\rangle$, or the coupling, as illustrated in fig 1a. Hence an analysis in the Fock basis predicts that the thermally averaged fringe visibility is largely reduced by dephasing. However, in the coherent state basis, the phase shift in the transmission amplitude depends strongly on the exact value of the coherent state, $|\nu\rangle$. This is illustrated in fig 1b, using just three coherent states as an example, but large variations in phase between different states is a general feature. Thus an analysis in the coherent state basis predicts that thermal smearing plays an important rôle in reducing the thermally averaged fringe visibility.

A steady-state theory, in which the cantilever is assumed to be in a thermal state, cannot distinguish between thermal smearing and dephasing and so cannot make predictions that depend on the cantilever basis. However, on theoretical grounds, there is good reason to choose the coherent state basis as the physically correct one in which to analyse the cantilever-dot interaction. This is because for a cantilever interacting with a thermal environment the coherent state basis is in some sense ‘selected’ by the interaction with the environment[4]. The selection of the coherent state basis by the environment is predicted as a result of a presumed linear coupling between the cantilever and the environment. An extension of the theory to the time-dependent regime offers the prospect of making predictions about current fluctuations in the system which should depend on the choice of cantilever basis states. Measurements of the fluctuations and comparison with a dynamic theory would then allow the selection of coherent states by the environment to be verified.

References

- [1] E. Buks et al., Nature 391 (1998) 871.
- [2] A.D. Armour and M.P. Blencowe, Phys. Rev. B 64 (2001) 035311
- [3] G. Mahan, *Many-Particle Physics*, (2nd edition, Plenum Press, New York, 1990).
- [4] W.H. Zurek, S. Habib and J.P. Paz, Phys. Rev. Lett 70 (1993) 1187

Figure Caption

Argument of the resonant elastic transmission amplitude as a function of $\kappa = \lambda/\hbar\omega$ for (a) the Fock states $n = 1, 10$ and 100 , (upper panel), and (b) the coherent states $\nu = (1/\sqrt{2})(1 - i)$, $\sqrt{5}(1 - i)$ and $\sqrt{50}(1 - i)$, (lower panel), with $\Gamma/\hbar\omega = 10$. The magnitudes of the coherent states are chosen so that the mean number of quanta in each correspond to one of the Fock states.

